- 1. THE ELECTRICAL WORK SHALL BE PERFORMED IN ACCORDANCE WITH THE LATEST IDOT STANDARDS, NATIONAL ELECTRICAL CODE AS WELL AS THE NATIONAL ELECTRICAL SAFETY
- 2. COORDINATE THE INSTALLATION OF TEMPORARY AND PERMANENT ROADWAY LIGHTING WITH THE CONSTRUCTION STAGING.
- 3. FOR POLE AND LUMINAIRE DETAILS. REFER TO ELECTRICAL PLANS AND SPECIFICATIONS.
- 4. COORDINATE THE INSTALLATION OF ROADWAY LIGHTING AND UNDERGROUND WORK WITH THE
- 5. CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTENANCE OF THE EXISTING AND PROPOSED LIGHTING DURING CONSTRUCTION. AS INDICATED ON THE PLANS AND AS DIRECTED BY THE
- 6. ALL REMOVED ISTHA POLES ARE TO BE RETURNED TO THE M-06 GARAGE, MARENGO-HAMPSHIRE EXIT ON I-90. AN A-14 WILL BE NEEDED WITH THE AMOUNTS. CONTRACTOR IS TO CALL MARK DALKA AT 630-399-0748 OR THE GARAGE x3506 PRIOR TO DELIVERY TO SET UP ASSISTANCE WITH UNLOADING MATERIAL.

LEGEND

IDOT ITEMS (IL-60)


- PROPOSED 47.5' M.H. LIGHT POLE WITH 400W M-C-III TYPE LUMINAIRE AND 8' DAVIT ARM
- PROPOSED 47.5' M.H. LIGHT POLE WITH 400W M-C-III TYPE LUMINAIRE AND 12' DAVIT
- o—Œ EXISTING PRIVATE ROADWAY LIGHTING UNIT TO REMAIN
- <u>~_</u>₹ RELOCATED PRIVATE ROADWAY LIGHTING UNIT
- PROPOSED 47.5' M.H. LIGHT POLE WITH 400W M-C-III TYPE LUMINAIRE AND 12' DAVIT
- PROPOSED TRAFFIC SIGNAL POST WITH 12' MAST ARM AND 400W M-C-III TYPE LUMINAIRE MOUNTED AT 47.5' (SEE TRAFFIC SIGNAL PLANS FOR EXACT POST LOCATION)
- PROPOSED 240/480V LIGHTING CONTROLLER, SINGLE PHASE, 60 HZ
- PROPOSED POLE MOUNTED ELECTRICAL SERVICE
- J PROPOSED JUNCTION BOX, EMBEDDED IN STRUCTURE, 12"x12"x6"
- GROUND ROD, 5/8" DIAMETER X 10 FT. >/.

PROPOSED 2" CONDUIT, PUSHED WITH 3*6 & 1*8 GROUND IN 1" UD

- PROPOSED UNIT DUCT IN TRENCH, SIZE AS NOTED
- PROPOSED CONDUIT EMBEDDED IN STRUCTURE, SIZE AS NOTED
- RGS RIGID GALVANIZED STEEL
- CONDUIT ATTACHED TO STRUCTURE
- EIS CONDUIT EMBEDDED IN STRUCTURE
- EIC CONDUIT ENCASED IN CONCRETE
- UD UNIT DUCT, 1", WITH 3*6 & 1*8 GROUND, UNLESS OTHERWISE NOTED
- EOP EDGE OF TRAVELLED PAVEMENT

ISTHA ITEMS (RAMPS & UNDERPASS)

EXISTING TOLLWAY LIGHT POLE TO REMAIN. 50' LIGHT POLE WITH 400W M-C-II TYPE LUMINAIRE WITH 15' MAST ARM



TEMPORARY LIGHT POLE WITH 400W LUMINAIRE AND 15' MAST ARM, SIZE AS NOTED

PROPOSED AERIAL CABLE, 4-1/C *6 WITH MESSENGER WIRE, UNLESS OTHERWISE NOTED

EXISTING ISTHA LIGHTING CONTROLLER

TEMPORARY ISTHA LIGHTING CONTROLLER

PROPOSED 150W UNDERPASS LUMINAIRE



SUMMARY OF QUANTITIES

 F.A.P. RTE.	SECTION	1	COUNTY		TOTAL SHEETS	SHEET NO.	
335	119R-2		LAKE		439	235	
STA.		· T(STA.				
FED. ROAD DIST. NO		ILLINOIS	FED. A	ID F	PROJECT		

60B01

ITEM NO.	ITEM DESCRIPTION	UNIT	IDOT QUANTITY	ISTHA QUANTITY	TOTAL QUANTITY
80400100	ELECTRIC SERVICE INSTALLATION	EACH	2	1 .	3
80700140	GROUND ROD, 5'8" DIA. X 10 FT.	EACH	37	-	37
81000600	CONDUIT IN TRENCH, 2" DIA., GALVANIZED STEEL	FOOT	60	-	60
81018500	CONDUIT PUSHED, 2" DIA., GALVANIZED STEEL	FOOT	1240	-	1240
81304100	JUNCTION BOX EMBEDDED IN STRUCTURE, 12" x 12" x 6"	EACH	4	-	4
81302000	JUNCTION BOX, CAST IRON, ATTACHED TO STRUCTURE, 4" X 4" X 3"	EACH	-	12	12
81302300	JUNCTION BOX, CAST IRON, ATTACHED TO STRUCTURE, 12" X 8" X 6"	EACH	-	2	2
81603170	UNIT DUCT, 600V, 3-1/C NO.6, 1/C NO.8 GROUND, (EPR-TYPE RHW), 1" DIA. POLYETHYLENE	FOOT	9180	_	9180
81603195	UNIT DUCT, 600V, 3-1/C NO.2, 1/C NO.2 GROUND, (EPR-TYPE RHW), 1 1/4" DIA. POLYETHYLENE	FOOT	60	-	60
81700110	ELECTRIC CABLE IN CONDUIT, 600V (EPR-TYPE RHW), 1/C NO. 10	FOOT	-	3000	3000
81700115	ELECTRIC CABLE IN CONDUIT, 600V (EPR-TYPE RHW), 1/C NO. 8	FOOT	-	125	125
81700225	ELECTRIC CABLE IN CONDUIT, 600V (EPR-TYPE RHW), 2-1/C NO. 6	FOOT	-	250	250
81800300	AERIAL CABLE, 3-1/C NO. 2 WITH MESSENGER WIRE	FOOT	· -	75	75
81800415	AERIAL CABLE, 4-1/C NO. 6 WITH MESSENGER WIRE	FOOT	-	9185	9185
81900200	TRENCH AND BACKFILL FOR ELECTRICAL WORK	FOOT	7665	-	7665
82102400	LUMINAIRE, SODIUM VAPOR, HORIZONTAL MOUNT, 400 WATT	EACH	42	16	58
83050730	LIGHT POLE, ALUMINUM, 47.5 FT. M.H., 8 FT. DAVIT ARM	EACH	14	-	14
83050805	LIGHT POLE, ALUMINUM, 47.5 FT. M.H., 12 FT. DAVIT ARM	EACH	26	-	26
83057435	LIGHT POLE, WOOD, 80 FOOT, CLASS 3, WITH 15FT MAST ARM	EACH	-	4	4
83600300	LIGHT POLE FOUNDATION, 30" DIAMETER	FOOT	296		296
83800205	BREAKAWAY DEVICE, TRANSFORMER BASE, 15 INCH BOLT CIRCLE	EACH	36	-	36
84200500	REMOVAL OF EXISTING LIGHITNG UNIT, SALVAGE	EACH	-	14	14
84200800	POLE FOUNDATION, REMOVED	EACH	1	14	15
84400105	RELOCATE EXISTING LIGHTING UNIT	EACH	1	-	1
84500110	REMOVAL OF LIGHTING CONTROLLER	EACH	-	1	1
84500120	REMOVAL OF ELECTRIC SERVICE INSTALLATION	EACH .	-	1	1
84500130	REMOVAL OF LIGHTING CONTROLLER FOUNDATION	EACH	-	1	1
JS811001 •	CONDUIT ATTACHED TO STRUCTURE, 3/4" DIA. GALVANIZED STEEL, PVC COATED	FOOT	-	20	20
JS811002 •	CONDUIT ATTACHED TO STRUCTURE, 1" DIA. GALVANIZED STEEL, PVC COATED	FOOT	-	720	720
JS811003 •	CONDUIT ATTACHED TO STRUCTURE, 1 1/2" DIA. GALVANIZED STEEL, PVC COATED	FOOT	-	125	125
JT821002 •	UNDERPASS LUMINAIRE, 150 WATT, HIGH PRESSURE SODIUM VAPOR	EACH	-	12	12
JS830030•	TEMPORARY WOOD POLE, 60 FT., CLASS 4	EACH	-	7	7
JS830034•	TEMPORARY WOOD POLE, 70 FT., CLASS 3, 15 FT. MAST ARM	EACH	-	12	12
JS846001•	MAINTAIN LIGHTING SYSTEM	L. SUM	-	1	-1
X0322695	MAST ARM, STEEL, STREET LIGHTING, 12 FT.	EACH	2	<u>.</u>	2
X0323792	LIGHTING CONTROLLER, SINGLE DOOR, CONSOLE TYPE	EACH	2	-	2
XX002113	TEMPORARY LIGHTING CONTROLLER	EACH	-	1	1
XX006767	LIQUIDTIGHT FLEXIBLE METAL CONDUIT, 3/4"	FOOT	-	20	20

• ISTHA PAY ITEM

LIST OF IDOT STANDARD DRAWINGS

877011 - STEEL COMBINATION MAST ARM ASSEMBLY AND POLE

LIST OF IDOT DISTRICT ONE STANDARD DRAWINGS

BE215 - LIGHTING CONTROLLER SINGLE DOOR BE220 - ELECTRIC SERVICE INSTALLATION AERIAL,

REMOTE DISCONNECT

BE301 - LIGHT POLE FOUNDATION, CONCRETE, <=35

FT. M.H. (15" B.C.)

BE330 - LIGHT POLE FOUNDATION ON CONCRETE PARAPET WALL

BE410 - LIGHT POLE, ALUMINUM, DAVIT TYPE, 47.5 FT. M.H.

BE701 - LUMINAIRE SAFETY CABLE ASSEMBLY BE702 - MISCELLANEOUS DETAILS, SHEET A - CABLE

SPLICE, POLE WIRING, TRENCH DETAIL

SHEET EL-01 OF 13 ILLINOIS DEPARTMENT OF TRANSPORTATION ILLINOIS RTE 60 OVER I-94

PROPOSED ROADWAY LIGHTING PLAN GENERAL NOTES, LEGEND AND QUANTITIES

SCALE: NONE DATE: MAY 8, 2007

REVISIONS

DESIGNED BY: JDM DRAWN BY: JDM CHECKED BY: